

SPECIFICATIONS FOR WSD DUMP BODY

Williamsen-Godwin's small dump bodies are perfect for landscaping and lighter duty hauling.

LENGTH: 8' to 12'

WIDTH: 96" O.D. standard

CAPACITIES: 2.1 to 5.8 cubic yards

SIDE CONSTRUCTION

12 ga. grade 50 high strength steel

3 bend dirt shedding top rail, 2" I.D. board pockets

Side heights of 12" and 16"

FRONT END

40" Front integral one piece 10 ga. 50,000 PSI min. bulkhead with pressed horizontal stiffener and tapered ¼ cab shield, window cut-out, full depth front corner pillars.

FLOOR CONSTRUCTION

7 gauge A1011 steel 2 bend floor with 7" deep rear apron at rear of body.

UNDERSTRUCTURE

7" tall 7 gauge 50,000 PSI steel one piece trapezoidal longitudinals.

Crossmemberless design.

TAILGATE

10 ga. 50,000 PSI min. steel inner panel and a 12 ga. 50,000PSI min. outer panel. Top of tailgate to be double sloping dirt shedding. Manual quick release tailgate with over lock hardware. 5/16 "drop and spreader chains. Standard 2-way operation. Tailgate heights of 18" and 22".

PAINT

Industry leading thermoset powder coating with thermoset zinc primer is STANDARD for all Williamsen-Godwin manufactured products.

ADDITIONAL OPTIONS

Fold down sides with single lever locking cam action mechanism, with hidden greaseable hinges

Steel or wood sideboards

Stainless steel body option

Sliding lever ditch gates

Manual spring return tarp system

10 ga. bolt on 6" rear spreader apron

Champion underbody hoist



WILLIAMSEN • GODWIN
TRUCK BODY CO.

www.williamsen-godwin.com

1.800.828.9847

1925 West Indiana Avenue • Salt Lake City, Utah 84104
Phone (801) 973-9400 • Fax (801) 973-2838

DISTRIBUTED BY:

