

HEAVY DUTY PUP TRAILER SPECIFICATIONS

Choose any Williamsen-Godwin dump body for your specific pup trailer application.

NUMBER OF AXLES	BODY LENGTH	GVW	AXLE CENTERS
2 AXLE	13 FT.	36,000	57"
3 AXLE	16 FT.	45,000	115"
4 AXLE	18 FT.	50,000	147"
5 AXLE	22 FT.	60,000	213"

FRAME

Constructed of 1/4" formed Strenx 100K psi steel channel with integral upper and lower crossmember gussets. 40" frame height for lower center of gravity.

HOIST

Trunnion mounted, single acting telescopic hoist, mounted in front of the body.

HOIST OPTIONS

Base mounted, inverted lift hoist
Inboard cylinder housing

TONGUE JACK

12,000 lb. capacity
Crank style with quick drop leg

AXLES

Axles are 5" round and have a 25,000 lb. capacity. 16" x 7" air brakes with ABS system.
Cams over tops of axles
Oil sealed, spring brakes on all axles
10 hole hub piloted hubs with cast steel drums and automatic slack adjusters.

AXLE OPTIONS


Self-steering axle with reverse alignment system.
Self steering, air-lift pusher or tag axles
Disc brakes

DRAWBAR

Tapered 1/4" Strenx 100K psi formed steel channels integral with frame. Rubber bushed swivel type eye stepped up on drawbar. All hydraulic and electrical lines routed inside frame and through drawbar. HD safety chains and holders for all air, electrical and hydraulic lines.

DRAW BAR OPTIONS

Premier HD poly bushed hinged drawbar. Air operated sliding drawbar with 72" or 90" travel, constructed of HD wall steel tube, air, electrical and hydraulic lines are routed to not interfere with sliding motion of the tongue.



SUSPENSION

Heavy duty, side of frame mounted hangars
25,000 lb. capacity per axle.
3-leaf springs
2,3, and 4 axle suspension

SUSPENSION OPTIONS

5 axle suspension
Single leaf springs

COATINGS

Epoxy primed
Urethane Top Coat
Cured at 190°

LENGTHS

Length from Pintle eye to rear axle:
2-axle 30'7"
3-axle 37'2"
4-axle 39'2"
5-axle 45'2"
Optional Drawbar length to maximize overall bridge



WILLIAMSEN • GODWIN
TRUCK BODY CO.

www.williamsen-godwin.com
1.800.828.9847

1925 West Indiana Avenue • Salt Lake City, Utah 84104
Phone (801) 973-9400 • Fax (801) 973-2838

DISTRIBUTED BY:

