

# SPECIFICATIONS FOR WGSD DUMP BODY

Maximize your payload with Williamsen-Godwin's Maxle Super Dump

**LENGTH:** 16' to 19'

**WIDTH:** 102" O.D. standard

**CAPACITIES:** Up to 30 cubic yards

## SIDE CONSTRUCTION

1/8" AR450 BHN 175/225K PSI quench and tempered abrasion resistant steel.

Boxed top rail, side and side stiffener formed from a single sheet to eliminate exterior horizontal welds.

Side heights of 50", 60" and 70"

## CYLINDER HOUSING:

HYVA pin to pin outboard mounted high pressure cylinder

## FRONT END

Sloping style, 1/8" AR450 BHN 175/225K PSI quench and tempered abrasion resistant steel.

One horizontal brace.

## UNDERSTRUCTURE

Crossmemberless design, 10" x 19# wide flange structural steel I-beam longitudinals. 1/4" full width asphalt designed rear cross bar with HD rectangular tube for added strength.

## FLOOR CONSTRUCTION

3/16" AR450 BHN 175/225K PSI quench and tempered abrasion resistant steel.

## TAILGATE

10 gauge 50,000 psi high strength steel, boxed perimeter, sloped bracing, two formed horizontal sloping center brace, 1/8" AR450 (175/225,000 KSI) high impact/abrasion resistant steel inner panel to form double wall.

Tailgate slopes forward 24 degrees.

Tailgate locks are air operated w/overlocking hardware.

## PAINT

Industry leading thermoset powder coating with thermoset zinc primer is STANDARD for all Williamsen-Godwin manufactured products.

## ADDITIONAL OPTIONS

Air operated folding mud flaps

Electric or manual tarp system.

Aluminum diamond plate fenders

Bed vibrator

Backup camera

Steel or hardwood sideboards

Rigid or folding ladders

Cab shield



**WILLIAMSEN • GODWIN**  
TRUCK BODY CO.

[www.williamsen-godwin.com](http://www.williamsen-godwin.com)

1.800.828.9847

1925 West Indiana Avenue • Salt Lake City, Utah 84104  
Phone (801) 973-9400 • Fax (801) 973-2838

**DISTRIBUTED BY:**

